

Viking External Shot Blasters

Features:

- These cylinder cleaning systems are chemical-free creating no disposal problems.
- Maximum Safety:
 - entry door safety lock-out
 - guarded cylinder lift table
- Easy Load/Unload
 - pneumatic door, cylinder loader and ejector.
- Low Maintenance /Long Life
 - Manganese alloy wear liners
 - variable speed tumbler
- Fast and Efficient
 - One operator can clean 15 average size cylinders per hour.
- Each model has: a blast wheel diameter of 18", a blast wheel horsepower of 10, a blast wheel RPM of 1725, blast motor and tumbler dr. RPMs of 1725, and ammeters.

Specifications:

	GC-	301	110	110/30	111	112	113	500	1000
Length		72"	107"	107"	112"	112"	114"	204"	258"
Depth		50"	42"	55"	80"	93"	42"	90"	90"
Height		74"	73"	84"	87"	109"	119"	111"	107"
Min. Diameter		6"	6"	6"	6"	6"	12"	12"	12"
Max Diameter		30"	20"	30"	20"	30"	36"	44"	44"
Max Length		30"	72"	72"	72"	72"	96"	120"	192"
No. of Wheels		2	2	2	2	2	4	6	8
Pneumatic Door		opt.	opt.	opt.	std.	std.	std.	opt.	opt.
Cylinder Loader		n/a	opt.	opt.	std.	std.	opt.	n/a	n/a
Cylinder Ejector		n/a	n/a	n/a	std.	std.	opt.	n/a	n/a
Var. Speed Tumbler		opt.	opt.	opt.	std.	std.	opt.	opt.	opt.
Digital Timer		opt.	opt.	opt.	std.	std.	std.	std.	std.
Analog Timer		std.	std.	std.	n/a	n/a	n/a	n/a	n/a
Blast Motor H.P.		2 @ 10	2 @ 10	2 @ 10	2 @ 10	2 @ 10	4 @ 10	6 @ 10	8 @ 10
Tumbler Dr. H.P.		1/2	1/2	1/2	1 1/2	1 1/2	1	2@ 1	2@ 1
Dust Coll. H.P.		3	3	3	3	3	3	5	2@ 3
Dust Coll. RPM		3450	3450	3450	3450	3450	2265	1980	2265
F/L Amps- 220v		61.6	61.6	61.6	64.6	64.6	117.2	177.8	234.4
F/L Amps- 440v		30.8	30.8	30.8	32.3	32.3	58.6	88.9	117.2

